


The information in this catalogue is subject to change without notice. The information and diagram in this catalogue reflect the technical features and configuration of the elevator model at press time (refer to the version number). In line with the principle of continuous development of products, our company reserves the right to change the selection of product technical parameters and colour at any time. The existing image technology cannot accurately reproduce the elevator component structure and decoration colour. Therefore, this catalogue only provides general information, not as a contract document. The specific configuration parameters are subject to the formal agreement.

If you need detailed information, please contact us.

Copyright: Hitachi Elevator (China) Co., Ltd





CONTENTS

Product Description


Digital and Intelligent Platform	01
Human Flow Predictive Elevator Operation	03
Intelligent and Exquisite Car	05

Standard Decoration

Gar Design (Normal Car) · · · · · · · · · · · · · · · · · · ·	09
Car Design (Deep / Wide Car) · · · · · · · · · · · · · · · · · · ·	13
Decoration Device	17

Solution Centre

Elevator Transportation System	23
Smart Management System · · · · · · · · · · · · · · · · · · ·	25
Contactless Elevator System	27
Elevator "Clean" Features	27
Emergency Rescue System · · · · · · · · · · · · · · · · · · ·	29



DIGITAL AND INTELLIGENT PLATFORM

New generation digital control system, featuring Hitachi's independently developed inverter, boasts a streamlined structure, intelligent efficiency, and incorporates multiple core technologies, comprehensively enhancing the safety and reliability of the elevator.



New generation integrating digital platform, highly intelligent and efficient



Core component pre-diagnosis technology, prevent failures



Intelligent auxiliary brake, improve reliability



New generation dual-medium communication system, provides dual protection

HUMAN FLOW PREDICTIVE ELEVATOR OPERATION

(APPLICABLE WITH FI-700 GROUP CONTROL)

By utilising advance image acquisition and analysis technology, predicting the human flow enables more efficient elevator operation that matches passenger's behavior.



Automatic Hall Call Registration By Sensor Detection

- Automatic recognition of passenger's position for intelligent hall call operation
- O Reduce waiting times, high efficiency




Passenger's Behavior Trend Prediction

- Automatic detection of passenger entering and exiting the elevator
- O Intelligent control of door opening and closing



Automatic Cancellation of Hall Call Registration

- Real-time feedback of passenger situation in the lift lobby
- O Hall call is cancelled when there is no passenger




- O Car space detection analysis
- Reduce avoidable stops through full-load intelligent travel



Number of Waiting Passengers Recognition

- Compute number of awaiting passengers
- O Intelligent dispatching operation



Group Control Human Flow Prediction

- Real-time human flow monitoring, evenly distribute the elevator calls
- Predict incoming human flow, dynamic computation of future trajectory
- O Shortens waiting times, reduces rate of long waits



INTELLIGENT AND EXQUISITE CAR

Creating a new aesthetic experience with the All New elevator decoration. Based on the design concept of "LESS IS MORE", simplifying complexity and creating a pure and gentle moving space. Displaying elevator information through graphics and text with real-time voice announcements, providing passengers a user-friendly elevator experience.

EXQUISITE CAR

Smart Elevator Car, All New Decoration

Create an overall elegant visual effect by introducing contour lighting design.



Ceiling with LED lighting, car walls incorporating stainless steel mirror finish



Stainless steel handrail



Innovative integrated car skirting LED recessed lighting









INTELLIGENT BROADCAST

LCD Display and Voice Announcements



Next 10 Floor



Door Opening



Door Closing



Please press the floor button



This elevator is overloaded. Will the last passenger please use the next lift.



Fire alarm. This elevator will return to the escape floor.



Fire alarm. Please evacuate as soon as the doors are open.





CAR DESIGN (NORMAL CAR)

E-220







Bare ceiling height	2450mm
False ceiling height	2400mm
Car ceiling	LM-220
Stainless steel mirro	r + Painted steel_WP71 (White)
	LED lighting
Car front return panel	
Car ironit return parier	Stainless steel hairline
Car transom	Stainless steel hairline Stainless steel hairline

Side wall (Front panel)	Stainless steel hairline
Side wall (Center panel)	Painted steel_YM47 (Champagne)
Side wall (Rear panel)	Painted steel_YM47 (Champagne)
Rear wall	Painted steel_YM47 (Champagne)
Car skirting illumination*	LED recessed lighting on both sides
Handrail AA-Y138, Stainle	ess steel hairline (Handrail at rear wall)
Car floor	S-693 Vinyl flooring

^{*} Applicable with LM-220 ceiling.

CAR DESIGN (NORMAL CAR)

E-220 Stainless Steel Hairline







Bare ceiling height	2450mm
False ceiling height	2400mm
Car ceiling	LM-220
Stainless steel	mirror + Stainless steel hairline
	LED lighting
Car front return panel	Stainless steel hairline
Car transom	Stainless steel hairline

Side walls		Stainless steel hairlin	ie
Rear wall		Stainless steel hairlin	ie.
Car skirting	illumination*	LED recessed lights on both side	es
Car door		Stainless steel hairlin	ie
Handrail	AA-Y138, Stainles	ss steel hairline (Handrail at rear wa	ll)
Car floor		S-693 Vinyl floorin	g

^{*} Applicable with LM-220 ceiling.

CAR DESIGN (NORMAL CAR)

E-71







Bare ceiling height	2450mm
False ceiling height	2450mm
Car ceiling	RF-056
	Painted steel_WN01 (Ivory white)
	LED lighting
Car front return panel	Stainless steel hairline
Car transom	Stainless steel hairline

Side walls	Stainless steel hairline
Rear wall	Stainless steel hairline
Car door	Stainless steel hairline
Car floor	A-26 Vinyl flooring

CAR DESIGN (DEEP / WIDE CAR)

E-220

(Deep Car

Standard





Bare ceiling height	2450mm
False ceiling height	2400mm
Car ceiling	LM-220
Stainless steel mirror + F	Painted steel_WP71 (White)
	LED lighting
Car front return panel	Stainless steel hairline
Car transom	Stainless steel hairline

Side wall (Front panel)	Stainless steel hairline
Side wall (Center panel)	Painted steel_YM47 (Champagne)
Side wall (Rear panel)	Painted steel_YM47 (Champagne)
Rear wall	Painted steel_YM47 (Champagne)
Car skirting illumination*	LED recessed lights on both sides
Car door	Stainless steel hairline
Handrail AA-Y138, Stainles	ss steel hairline (Handrail at rear wall)
Car floor	S-693 Vinyl flooring

^{*} Applicable with LM-220 ceiling.

E-220 Stainless Steel Hairline

Deep Car

(Optional)





Bare ceiling height	2450mm
False ceiling height	2400mm
Car ceiling	LM-220
Stainless steel	mirror + Stainless steel hairline
	LED lighting
Car front return panel	Stainless steel hairline
Car transom	Stainless steel hairline

Side walls	Stainless steel hairline	
Rear wall	Stainless steel hairline	
Car skirting illumination*	LED recessed lights on both sides	
Car door	Stainless steel hairline	
Handrail AA-Y138, Stainles	AA-Y138, Stainless steel hairline (Handrail at rear wall)	
Car floor	S-693 Vinyl flooring	

^{*} Applicable with LM-220 ceiling.

CAR DESIGN (DEEP / WIDE CAR)

E-220

(Wide Car

Standard





Bare ceiling height 2450mm	
False ceiling height	2400mm
Car ceiling	LM-220
Stainless steel mirror + Painted steel_WP71 (White)	
	LED lighting
Car front return panel	Stainless steel hairline
Car transom	Stainless steel hairline

Side wall (Front panel)	Stainless steel hairline
Side wall (Rear panel)	Painted steel_YM47 (Champagne)
Rear wall	Painted steel_YM47 (Champagne)
Car skirting illumination*	LED recessed lights on both sides
Car door	Stainless steel hairline
Handrail AA-Y138, Stainless steel hairline (Handrail at rear wall)	
Car floor	S-693 Vinyl flooring


^{*} Applicable with LM-220 ceiling.

E-220 Stainless Steel Hairline

(Wide Car

Optional





Bare ceiling height	2450mm
False ceiling height	2400mm
Car ceiling	LM-220
Stainless steel mirror + Stainless steel hairline	
	LED lighting
Car front return panel	Stainless steel hairline
Car transom	Stainless steel hairline

Side walls	Stainless steel hairline	
Rear wall	Stainless steel hairline	
Car skirting illumination*	LED recessed lights on both sides	
Car door	Stainless steel hairline	
Handrail AA-Y138, Stainles	drail AA-Y138, Stainless steel hairline (Handrail at rear wall)	
Car floor	S-693 Vinyl flooring	

^{*} Applicable with LM-220 ceiling.



DECORATION DEVICE

Car Operating Panel Normal Car (Hinge Type)

(5) (8) (4) (2)

3 11

2 10

8 8 9

Car Operating Panel
Deep/Wide Car
(Surface Mounted Type)

Button



Colour LCD

O Button
WL-MWB



GOP-199

• Indicator Colour LCD

ButtonWL-MWB

WL-MWB

Dimension

Ф36mm

Material

Rim: Stainless steel brushed Faceplate: Circular stainless steel hairline

Illumination

Symbol and periphery lighted up in white

 Button with braille is available as option for maximum 2 digits



"Door Close" Button

(Without illumination)



"Door Open" Button

(Without illumination)



"Floor"
Button
(Without illumination)



"Floor"
Button
(With illumination)








Landing Door

Painted steel_WN01 (Ivory white)

Landing Jamb

AS-1X narrow type: Painted steel_WN01 (Ivory white)





At First Floor

• Landing Door

Stainless steel hairline

Landing Jamb

AS-1X narrow type: Stainless steel hairline







VIB-820W

Hall Operating Panel

Indicator

Monochrome LCD

Faceplate Material


Stainless steel hairline

Button

WL-MWB

Mounting


Surface-mount type





ELEVATOR TRANSPORTATION SYSTEM

Human Flow Prediction Analysis

- Real-time monitoring and intelligent dispatching, evenly distribute the elevator calls
- O Analyse overall human flow prediction, dynamic adjustment of future trajectory
- O Shortens average waiting times, reduces rate of long waits








Rush Hour Schedule Operation

O During preset rush hour interval, the system automatically predicts the human flow and assign elevators to concentrate services on floors with heavy traffic.

conference

O During up-peak rush hour interval, the system automatically predicts the flow of people taking elevators and dispatches elevators to provide centralised service at the base floor.



Destination Floor Reservation System, DFRS

Each passenger registers their destination floor on the registration device located at the landing hall and know in advance the designated elevator to take. System assigned one elevator for the passengers with the same destination floor. This reduces the number of stops, achieves traffic diversion, improves operational efficiency, and reduces waiting time.

VIP Service

Used for serving VIP passengers in the building. When a VIP signal is received, the system will assign one elevator to break away from group control and provide dedicated service for the VIP passengers, by transporting them directly to the destination floor.

SMART MANAGEMENT SYSTEM

01

Elevator Computer Monitoring System

Elevator computer monitoring system can be installed at the locations specified by the customer (Such as fire control room, building management office etc.) to monitor the running status of multiple elevators to provide optimal services to passenger.

02

Live Feed Broadcast

Through the car multimedia LCD indicator connected to the building live feed broadcast system, information specified by customer can be displayed.

8 (2) \$ (1) 4 (1) 3 (3) 2 (8) 1) (7)

(h) (h)





Nighttime Protective Operation

During specified nighttime hours, elevator will travel directly to the designated floor without responding to any hall calls to ensure the safety of the passengers.

Visual Intercom

Elevator authorisation for visitor access or resident visits can be achieved through a visual intercom system. Residents can also use the indoor unit to obtain basic elevator operation status information or call the elevator.





BYPASS


CONTACTLESS ELEVATOR SYSTEM

01

Elevator Registration via Bluetooth

Passengers connect to the elevator via smartphone Bluetooth signals for verification. The elevator will be registered according to the authorised preset floor.







19 Elevator Registration via Medium Devices

Passengers use an IC card or a QR code generated through WeChat to call the elevator, without any contact with the elevator buttons. This effectively prevents the elevator buttons from becoming a virus transmission source.









ELEVATOR "CLEAN" FEATURES

01

Antibacterial Button

By adding highly efficient antibacterial ions to the button surface, residual bacteria on the buttons can be effectively suppressed, ensuring passenger safety. Hitachi antibacterial buttons have been certified by SGS, with an antibacterial rate of over 99% against Escherichia coli and Staphylococcus










2 Ultraviolet, UV Sterilisation

This function automatically detects and controls the ultraviolet sterilisation and disinfection lamp inside the car when the elevator is at idle (With no passenger) state, to achieve all-round sterilisation in the car.



EMERGENCY RESCUE SYSTEM

Power Failure Emergency

Car Emergency Lighting

In the event of power failure, the car emergency lighting will be lighted up automatically.

Automatic Rescue Device (ARD)

In the event of power failure, elevator powered by the automatic rescue device (ARD) will run to the nearest service floor at slow speed, levelled and stop at the landing with door open to prevent passengers from being trapped.

Building Generator Operation

During power failure, the power supply system of the elevator will switch to building generator power automatically to maintain continuous operation of elevators.









Automatic Rescue Device (ARD)

Building Generator Operation

Fire Emergency



Fire Emergency Operation

Upon receiving the fire signal, the elevator will automatically home to the fire return floor with its door open to let the passengers out. This ensure the safety of the passengers in the elevator.

Fireman Operation

After the elevator reaches the fire return floor with its door open, the fireman can use the elevator to perform rescue.



Interphone System


When passenger presses the emergency call button on the car operating panel, they can communicate with the management in the machine room or monitoring center.

"What happen?"

"What's wrong?"

Earthquake Emergency Operation

When an earthquake is detected, the elevator system controls the running elevator to stop and levelled at the nearest service floor with its door open, to ensure the safety of passengers.



Pit Flood Operation

When there is water ingress in the pit and float switch is activated, the elevator will operate under pit flood control mode. The elevator will travel up to the evacuation floor and open the door for the passengers to leave. The elevator can only resume normal operation after the float switch is manually reset.





